

## In Screed DTIE-10 Heating Cable

### Applications

- This product is specifically designed for heating timber floor surfaces
- Direct acting underfloor heating systems
- Background underfloor heating systems
- Soil warming, ice and snow melting and frost protection of pipes



**Deviflex™ DTIE-10** has an earth screen for installation in thin screed toppings, over and under wooden floors, over insulation and for use in Devicell - under floating timber floors.

Also used for soil warming and frost protection of pipes.

# In Screed DTIE-10 Heating Cable

## Features

- 10 W/m
- Twin conductor
- Very low EMF
- One cold tail for ease of installation
- Lead and PVC free
- Flexible
- Soft
- Metre marking

## Technical Data

Cable construction	Single conductor
Rated voltage	240
Watts per meter	10
Watts per square meter	N/A
Diameter	6mm
Sheat	Polyolefin
Cold Tail Length	3m
Pulling strength	120N
Deformation strength	2,000N
Max. temperature	70°C
Warranty	10 years
Direct heating in concrete floors	x
Storage heating in concrete floors	x
Heating in renovated and thin floors	✓
Heating in wooden floors	✓
Freezers	✓
Frost protection	✓
Ice & snow melting	✓

## Stock Program

Code No.	Watts	Length	Cold Tail
89825380	22	2m	1.5mm <sup>2</sup>
89825382	44	4m	1.5mm <sup>2</sup>
89825384	65	6m	1.5mm <sup>2</sup>
89825386	87	8m	1.5mm <sup>2</sup>
89825388	110	10m	1.5mm <sup>2</sup>
89825390	165	16m	1.5mm <sup>2</sup>
89825392	215	20m	1.5mm <sup>2</sup>
89825394	325	30m	1.5mm <sup>2</sup>
89825396	435	40m	1.5mm <sup>2</sup>
89825398	545	50m	1.5mm <sup>2</sup>
89825400	655	60m	1.5mm <sup>2</sup>
89825402	760	70m	1.5mm <sup>2</sup>
89825404	870	80m	1.5mm <sup>2</sup>
89825406	980	90m	1.5mm <sup>2</sup>
89825408	1,090	100m	1.5mm <sup>2</sup>
89825410	1,305	120m	1.5mm <sup>2</sup>
89825412	1,525	140m	1.5mm <sup>2</sup>
89825414	1,740	160m	1.5mm <sup>2</sup>
89825416	1,960	180m	1.5mm <sup>2</sup>
89825418	2,175	200m	1.5mm <sup>2</sup>